



INSTRUCTIONS FOR USE AND MAINTENANCE

Sealing Sheets

PRODUCT DESCRIPTION:

Rubber sealing sheets are manufactured on the basis of synthetic and natural rubbers, they have various properties determined by the use of special synthetic rubbers, rubber fillers and additives. They are used as a semi-finished product for the further production of sealing and damping components.

STORAGE:

Temperature: ideal temperature: From +5 °C to +25 °C, permitted range -10 °C to +40 °C (depending on type, however long-term preferably lower). Do not store near heat sources (radiators, steam pipes). The room must be protected against moisture, condensation and direct weather exposure. Rubber floors must be protected from direct sunlight and strong artificial light containing UV components. Rubber rolls should be stored freely standing in an upright position. If stored flat, they must not be loaded with other heavy material in order to prevent permanent deformation. Rubber must not come into contact with oils, fats, solvents or other aggressive chemicals. The storage area should not contain ozone-generating equipment (electric motors, high-voltage equipment), as ozone causes rubber cracking.

CARE AND CLEANING:

Clean using a sorghum broom or a horsehair brush. No hard objects such as wire brushes may be used. They may be cleaned with a soap solution. They must not come into contact with any acids, alkalis or solvents.



BOGUMA, s.r.o.

Továrenská 314, 956 18 Bošany, Slovenská republika
Zapísaná v OR OS Trenčín, oddiel ~~Sro~~, vložka č. 19109/R
IČO: 35 922 087, IČ DPH: SK2021963625

Bankové spojenie: SK12 1100 0000 0029 4107 3171, SWIFT: TATRSKBX

Tel.: +421 38 5426 307, +421 38 5426 308, sales@boguma.sk, www.boguma.sk