

# RUBBER SHEETING PARA QUALITY 7689 — NR



<b>INTERIOR</b>	1	<b>g/cm<sup>3</sup></b>	-25 - +70	<b>°C</b>	40 +/- 5	<b>Sh A</b>	600	<b>%</b>	12	<b>MPa</b>	1-10	<b>mm</b>
<b>ENVIRONMENT</b>	<b>DENSITY</b>	<b>TEMPERATURE RANGE</b>	<b>HARDNESS</b>	<b>ELONGATION</b>	<b>TENSILE STRENGTH</b>	<b>THICKNESS</b>						

Sealing plate high-strength and highly elastic with increased abrasion resistance. Made on the basis of natural rubber NR with various physical and mechanical properties. With the possibility of specifying the thickness (1 - 10 mm), width (1,200 - 1,400 mm) and number of inserts (0 - 2 pcs). Click and choose. Complete the exact specification in the configurator.



## RESISTANCE

- Abrasion resistance **HIGHLY RESISTANT**
- Weather resistance **NO**
- Ozone resistance **NO**
- UV resistance **NO**
- Alkaline resistance **MEDIUM RESISTANT**
- Acid resistance **MEDIUM RESISTANT**
- Oil resistance **NO**
- Gasoline resistance **NO**

## CONFIGURATION OPTIONS

### THICKNESS

- 1 mm (+/- 0,2 mm)
- 1.5 mm (+/- 0,2 mm)
- 2 mm (+/- 0,2 mm)
- 3 mm (+/- 0,3 mm)
- 4 mm (+/- 0,4 mm)
- 5 mm (+/- 0,5 mm)
- 6 mm (+/- 0,5 mm)
- 8 mm (+/- 0,8 mm)
- 10 mm (+/- 0,8 mm)

### WIDTH

- 1200 mm (+/- 10 mm)
- 1400 mm (+/- 10 mm)

### LENGTH

- 20 m (+/- 200 mm)
- 10 m (+/- 200 mm)

### NUMBER OF REINFORCEMENT LAYERS

- without reinforcement (for thicknesses 1 - 10 layers mm)