

9001 — CR-NR

RUBBER SHEETING SOUNDPROOF 9001 —  
CR-NR

INTERIOR	2,44	g/cm <sup>3</sup>	-25 - +80	°C	65 +/- 5	Sh A	100	%	3	MPa	2.5	mm
ENVIRONMENT	DENSITY		TEMPERATURE RANGE		HARDNESS		ELONGATION		TENSILE STRENGTH		THICKNESS	

Sealing plate made of a special self-extinguishing material with acoustic properties of a sound barrier. Designed for use without demands for resistance to negative environmental influences and without mechanical stress. Made on the basis of CR and NR rubbers with slight resistance to acids, alkalis and oils. In standard thickness 2.5 mm and width max 1,400 mm. Complete the exact specification in the configurator.



## RESISTANCE

Alkaline resistance MEDIUM RESISTANT  
Acid resistance MEDIUM RESISTANT  
Oil resistance MEDIUM RESISTANT

## CONFIGURATION OPTIONS

## THICKNESS

2.5 mm (+/- 0,3 mm)

## WIDTH

1200 mm (+/- 10 mm)

## LENGTH

10 m (+/- 200 mm)

## NUMBER OF REINFORCEMENT LAYERS

without reinforcement (for thicknesses 2.5 mm)  
layers

9001 — CR-NR

RUBBER SHEETING SOUNDPROOF 9001 —  
CR-NR

## SOUND LOSS TM E-90

