

ELECTRICAL INSULATING MATTING CLASS 4 SMOOTH - Ho




4 mm	6.1 kg/m ²	65 +/- 5 Sh A	INTERIOR
THICKNESS	BASIS WEIGHT	HARDNESS	ENVIRONMENT

Top side - smooth surface



Bottom side - cloth impression



ADDITIONAL INFORMATION

As standard, we supply rolls 1 or 1,2 m wide and 10 m long. However, we can also provide custom cuts: 0,6x0,6 m; 0,6x1m; 1x1m; 1,2x1m or others.

RESISTANCE ACCORDING TO IEC 61111:2009

Mechanical puncture resistance	YES
Test for slip resistance	YES
Dielectric tests according given class	YES
Ageing tests	YES
Low temperature folding test	YES
Flame retardance test	YES
Oil resistance	YES
Acid resistance	YES

Electrical insulating matting certified according to IEC 61111:2009 in class 4, with an operating voltage of 36,000 V, a test voltage of 40,000 V and a withstanding voltage of 50,000 V, with permanently vulcanized marking tape. Vulcanized elastomer smooth is available in gray color, 4 mm thick (+0.6/-0.2mm) with basic weight 6.1 kg/m².

CONFIGURATION OPTIONS

THICKNESS

4 mm (+ 0,6/- 0,2 mm)

WIDTH

1000 mm (+/- 10 mm)

1200 mm (+/- 10 mm)

LENGTH

10 m (+/- 200 mm)