
S4 — SBR+ Flame retardant


RUBBER FLOORING WIDE RIBBED PATTERN — S4-N

INTERIOR	80 +/- 5 Sh A	6 mm	5.9 kg/m²
ENVIRONMENT	HARDNESS	THICKNESS	BASIS WEIGHT



Bottom side - cloth impression











RESISTANCE

Flame retardant	YES
Abrasion resistance	HIGHLY RESISTANT
Weather resistance	NO
Ozone resistance	NO
UV resistance	NO
Alkaline resistance	NO
Acid resistance	NO
Oil resistance	NO
Gasoline resistance	NO

Rubber roofing for interior surfaces. Durable and low maintenance with easy handling. With a wide ribbed type S4, in black color. This flooring is flame retardant according to EN 13501 C_{fl}-s1. In standard thickness 6 mm. It weighs 5.9 kg / m2. Specify in the configurator.
This classification is valid for the following end use conditions: - Flooring laid on the any substrates of reaction to fire class $A1_{fl}$ or $A2_{fl}$.

CONFIGURATION OPTIONS

THICKNESS

6 mm (+/- 0,5 mm)

WIDTH

1230 mm (+/- 10 mm)

LENGTH

10 m (+/- 200 mm)

BOGUMA, Ltd., Továrenská 314, 956 18 Bošany, Slovak Republic
Business Register Record, Trenčín, Section Ltd., Record No. 19109/R
IČO: 35 922 087, IČ DPH: SK2021963625
Billing Information: SK52 0900 0000 0052 4549 4451, SWIFT: GIBASKBX
Tel.: +421 38 5426 307, +421 38 5426 308, sales@boguma.sk, www.boguma.sk