


S8 — SBR+ Flame
retardant

RUBBER FLOORING COIN PATTERN — S8-N



INTERIOR 80 +/- 5 **Sh A** 4 **mm** 5.9 **kg/m²**
ENVIRONMENT **HARDNESS** **THICKNESS** **BASIS WEIGHT**



Bottom side - cloth impression



RESISTANCE

Flame retardant	YES
Abrasion resistance	HIGHLY RESISTANT
Weather resistance	NO
Ozone resistance	NO
UV resistance	NO
Alkaline resistance	NO
Acid resistance	NO
Oil resistance	NO
Gasoline resistance	NO
Mechanical puncture resistance	YES
Test for slip resistance	YES
Dielectric tests according given class	YES
Ageing tests	YES
Low temperature folding test	YES
Flame retardance test	YES
Oil resistance	YES
Acid resistance	YES

Rubber roofing for interior surfaces. Durable and low maintenance with easy handling. With a coin pattern (round stud) type S8, in black color. This flooring is flame retardant according to EN 13501 C_{fl}-s1. In standard thickness 4 mm. It weighs 5.9 kg / m². Specify in the configurator.

This classification is valid for the following end use conditions: - Flooring laid on the any substrates of reaction to fire class A1_{fl} or A2_{fl}.

CONFIGURATION OPTIONS

THICKNESS

4 mm (+/- 0,3 mm)

WIDTH

1230 mm (+/- 10 mm)

LENGTH

10 m (+/- 200 mm)